

## STATOJETS AND ACCESSORIES

Statojet performances									
Pressure (in bars)	Flow in L/h								
	360°			300°			240°		
	20	32	50	20	32	50	20	32	50
Effective range in metres									
1.0	1.3	1.5	2.0	1.7	2.3	2.8	1.8	2.4	3.0
1.5	1.5	1.7	2.2	2.2	2.8	3.4	2.4	2.8	3.4
2.0	1.6	1.9	2.4	2.2	3.0	3.8	2.4	3.1	3.9

## STANDARD TURBO WB MICRO SPRINKLERS

Maximum range (in metres)	Models	
	76 L/h	99 L/h
	3.9	4.6
Pressure (in bars)	Sprinkler flow	
1	61	80
2	89	115

## PRESSURE COMPENSATING WB MICRO-SPRINKLERS

Maximum range (in metres)	Models			
	FC 36 L/h	FC 47 L/h	FC 56 L/h	FC 90 L/h
	2	2.2	2.2	4.3
Pressure (in bars)	Sprinkler flows (in L/h)			
1	35	47	53	
2	36	47	56	88
2.8	36	47	56	89

## ROTATORS

		R2000				R2000 WF		
		Flow control		Standard				
Nozzle type		Auto FC 1.25	Auto FC 2.0	Orange 11/128	Violet 3/32	Yellow 13/128	Red 1/8	Gold 9/64
		K3 9°	K4 24°	K3 9°	K3 24°	K4 24°	24°	24°
Flow in L/h	2 bars			260	310	365	560	716
	2.5 bars			290	350	410	625	795
	3 bars	284	455	320	380	450	685	869
	3.5 bars			350	410	490	740	940
	4 bars			375	440	520	790	1001
Average range		8 m	10 m	7.3 to 8.2 m	10 to 10.7 m	10 to 10.7 m	12.2 to 12.8 m	12.5 to 13.1 m